BAR CODE SCANNERS

Speed and versatility combine for increased productivity at checkout

The LS9208 presentation scanner from Symbol Technologies delivers both a high-performance processor and an innovative 100-line rastering omni-directional scan pattern for increased productivity at checkout, resulting in higher customer satisfaction.

Built for both speed and versatility, the LS9208 features a small footprint, choice of colors and an optional, adjustable multi-mount stand that is easily adaptable to many point-of-sale environments, such as:

Environment:	Applications:
Retail (convenience stores, grocery stores, department stores, specialty hard and soft goods stores)	Customer checkout EAS tag deactivation Back room applications
Pharmacies and drug stores	Customer checkout EAS tag deactivation Prescription verification Distribution and management of controlled substances
Other	Time and attendance Library Office automation

Robust new features offer easy set up and reduced costs

With the 123Scan setup utility, programming and configuring the LS9208 is made easy and minimizes startup time wherever the scanner is used. What's more, multiple onboard interfaces and universal cables further reduce your inventory requirements. For the most investment protection, the LS9208 also features built-in shock absorption that adds unmatched durability for a scanner in this class. The LS9208 offers premium features and powerful performance to help you save time and money.

Today's most advanced presentation scanner from a global leader

In many applications, the feature-rich LS9208 presentation scanner offers aggressive performance, maximum durability and optimal ergonomics to create a more productive POS environment. When you buy the LS9208, you receive the added assurance of purchasing from Symbol — a company with proven solutions and millions of scanner installations worldwide.

To learn how the LS9208 presentation scanner can work for you, or to find out more about Symbol's products and solutions, contact us at +1.800.722.6234 or +1.631.738.2400, or visit www.symbol.com/ls9208



ATURES	BEN

High-performance, 100-line rastering omni-directional scan pattern

Single line scan pattern

Multiple onboard interfaces

Universal cables

Small footprint

Adjustable, multimount stand

Built-in shock absorption

Flash memory

Checkpoint Electronic Article Surveillance (EAS) deactivation option

Supports 123Scan setup utility

Reads Reduced Space Symbology® (RSS)

Global Trade Item Number (GTIN) Compliant

Advanced Data Formatting (ADF)

Increased productivity for novice and expert users resulting in shorter checkout lines, better customer service

Perfect for reading bar code menus and pick lists

Flexible host connectivity protects your hardware investment

Allows for easy replacement and/or upgrades

Fits into the tightest cash/wrap

Optimize operator comfort and efficiency

Protects scan module assembly increasing durability

Facilitates updates/customization of product in the field

Integrated antenna saves valuable counter space

Flexible setup using PC download

Compatibility with new symbology leverages your hardware

Capable of decoding and transmitting 14-digit GTINs, where appropriate

Enables users to modify data prior to sending to host computer, eliminating costly modifications to the host software



LS9208 Specification Highlights

Physical Characteristics

Physical Characteristics	
Dimensions:	Scanner only: 5.51 in H x 3.49 in W x 2.96 in. D 14 cm H x 8.8 cm W x 7.5 cm D With adjustable stand: 7.18 in H x 4.83 in W x 3.73 in. D/ 18.24 cm H x 12.27 cm W x 9.47 cm D
Weight:	Scanner only: 10.2 oz/320 g With adjustable stand: 21.5 oz/670 g
Power Source:	Power drawn from Host terminal or external power supply; depends on Host type.
Voltage:	5.0 VDC +/- 10%
Nominal Current:	390 mA
Power:	2 Watts
Mounting Options:	Adjustable multi-mount stand
Color:	Cash Register White or Twilight Black
Performance Characteris	tics
Light Source:	650 nm visible laser diode
Roll (Tilt):1	Omni-directional: 360° Single scan line: +/- 40°
Pitch: ²	Omni-directional: +/- 50° Single scan line: +/- 60°
Skew (Yaw): ³	Omni-directional: +/- 50° Single scan line: +/- 50°
Print Contrast:	25% minimum reflective difference
Scan Patterns:	Omni-directional: 20 interlocking lines, 5 scan angles, 4 lines per angle rastering @ 5Hz Single scan line capability
Scan Rate:	Omni-directional: 1500 scans per second Single scan line: 75 scans per second
Depth of Field:	0-9 in./0-22.9 cm @ 13 mil (100 % UPC/EAN)
Nominal Working Range:	5 mil (38%) 1-2.5 in./2.5-6.4 cm 7.8 mil (60%) 0-6 in./0-15.2 cm 10.4 mil (80%) 0-7.5 in./0-19 cm 13 mil (100%) 0-9 in./0-22.9 cm
Width of Field:	1.6 in./40 mm @ Face 6.7 in./170 mm @ 9 inches
Minimum Resolution:	5 mils

UPC/EAN/JAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 128, ISBT 128, Code 39, Code 39 Trioptic, Interleaved 2 of 5, Discrete 2 of 5, Code 93, Code 11, Codabar, MSI, RSS variants
USB, RS232, IBM® 468X/9X, Keyboard Wedge, Wand and Synapse™ (allows connectivity to virtually every POS host type)
32° to 104°F/0° to 40°C
-40° to 158°F/-40° to 70°C
5% to 95% noncondensing
Withstands repeated 4 ft/1.2 m drops to concrete
Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor and Sodium Vapor: 450 ft-candles (4,844 LUX) Sunlight: 8,000 ft-candles (86,111 LUX)
Optional Checkpoint Electronic Article Surveillance EAS
Certified to UL 1950, CSA C22.2 No. 950 EN60825
CDRH Class IIa Laser Product IEC 60825 Class 1 Laser Product
CISPR B, FCC B

Warranty

The Symbol LS9208 Omni-directional scanner is warranted against defects in workmanship and materials for a period of 30 months from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See the complete warranty for details.

- 1. Roll (Tilt): Controlled by rotating the wrist clockwise or counter-clockwise
- 2. Pitch Controlled by dropping or raising the wrist
- Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa
 The above performance characteristics refer to 100% UPC bar code at 80% contrast located at 4 in/10 cm from nose of the scanner.

About Symbol Technologies -

Symbol Technologies, Inc., The Enterprise Mobility CompanyTM, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading retailers, transportation and logistics companies, manufacturers, wholesale and distribution centers, government agencies and healthcare facilities. More information is available at www.symbol.com



Corporate Headquarters
Symbol Technologies, Inc.
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722-6234
+1.631.738.2400
FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
(Singapore Branch)
Asia Pacific Division
230 Victoria Street #12-06/10
Bugis Junction Office Tower
Singapore 188024
TEL: +65.6796.9600
FAX: +65.6796.7199

For Europe, Middle East and Africa Symbol Technologies EMEA Division Symbol Place, Winnersh Triangle Berkshire, England RG41 5TP TEL: +44.118.9457000 FAX: +44.118.9457500 For North America, Latin America and Canada Symbol Technologies The Americas One Symbol Plaza Holtsville, NY 11742-1300 TEL: +1.800.722.6234 +1.631.738.2400 FAX: +1.631.738.5990

Symbol Web Site

For a complete list of Symbol subsidiaries and business partners worldwide contact us at:

www.symbol.com

E-mail info@symbol.com



DS-I S9208 09/0

Part No. DS-LS9208 Printed in USA 09/06 © Copyright 2006 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol* is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.